

Home ■ Soluções ■ Plantas para Tratamento de Esgoto ■ Micro-Peneiramento e Filtração ■  
Filtragem de efluente tratado biologicamente

## HUBER Solutions for Filtration of Biologically Treated Wastewater



Filtration of biologically treated wastewater serves for removal of suspended solids (*suspensa*) remaining in clarifier effluents. Such *suspensa* contain about 50 % carbon, almost 10 % nitrogen and over 1 % phosphorus.

Around 1 mg/L (ppm) of phosphorus remain in the effluent, even if the biological treatment stage is designed for enhanced biological phosphorus removal and/or chemical phosphorus precipitation. Subsequent filtration is necessary where stringent phosphorus limits must be reliably maintained.

- Our **RoDisc® Rotary Mesh Screen** is provided with fabric of a mesh size between 0.01 and 0.1 mm. The fabric is applied on both sides of slowly rotating discs.
- Wastewater flows continuously upstream through our **Sand Filter**, and its sand bed is continuously backwashed.
- **Membrane Bio-Reactors** perform biological treatment and filtration. Our Membrane Filters retain not only all solids but also all bacteria within the bio-reactor.

**HUBER DO BRASIL SOLUÇÕES EM TRATAMENTO DE ÁGUA E EFLuentes LTDA**

Rua João Alvares Soares, 1447 - Campo Belo - São Paulo - CEP: 04609-003

Tel: 00 55 11- 2614-1610 FAX: 00 55 11 2614-1610 ext: 205 Internet: [www.huber-technology.com.br](http://www.huber-technology.com.br)